

## CARE AND MAINTENANCE

### Door Furniture

At twelve (12) monthly intervals, the fixing screws securing the furniture to the door, both surface fix and through fix, should be checked and tightened as required. Loose fitting furniture which fails will not be covered under warranty.

All door furniture should only be wiped clean with a soft damp cloth. In the case of Satin Stainless Steel or Satin Chrome Plate, a non-abrasive mild household detergent may be used to remove ingrained grime.

### Locks & Latches

Care should be taken to ensure the internal components are kept free of dirt and woodchips during installation as this is the most common cause of malfunction and will not be covered under warranty. Tubular latches used in external situations should be lubricated by an aerosol lubricant at twelve (12) monthly intervals.

### Note

For applications that are subject to high use/ abuse or in corrosive environments, additional preventative maintenance will be required at a minimum of three (3) monthly intervals.

## WARRANTY

Our goods come with guarantees that cannot be excluded under the local consumer law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.



# Medio & Form Series

Passage and Privacy

## INSTALLATION INSTRUCTIONS

Featuring QuickFix™

### Box contents

- Rose & lever set - contains 2 factory fitted screws
- Strike
- Latch
- Pack of 6 fixing screws (includes 2 anti-rotational screws)
- Jig template

### Door thickness

- Passage set 30mm – 50mm
- Privacy set 30mm – 42mm

### Tools required

- Tape measure
- Pencil
- Level
- Drill
- Drill bits - 4mm & 8mm
- Spade bit - 25mm
- Hammer
- Chisel
- Screwdriver (Phillips)

Allegion (Australia) Pty Ltd  
Freephone 1800 098 094  
Email [auinfo@allegion.com](mailto:auinfo@allegion.com)  
[www.allegion.com.au](http://www.allegion.com.au)

Allegion (New Zealand) Limited  
Freephone 0800 477 869  
Email [nzinfo@allegion.com](mailto:nzinfo@allegion.com)  
[www.allegion.co.nz](http://www.allegion.co.nz)




Scan here for more information on installing Schlage Medio Series with QuickFix™




## 1. DOOR PREPARATION

Measure 970mm from floor, on door and jamb.




## 2. DRILL PILOT HOLES

Using the jig, mark and drill 2x Ø4mm pilot holes (and optional privacy) from both sides of the door.




## 3. DRILL HOLES

Re-drill Ø8mm holes and Ø25mm spindle hole on both sides of the door. Drill barrel hole Ø24x85mm.




## 4. PREPARE & INSTALL LATCH

Use latch as guide to mark and chisel latch recess. Install latch to ensure the curved latch bolt faces the door jamb. Drill pilot holes and screw in latch.




## 5. PREPARE JAMB & INSTALL STRIKE

Measure Ø8mm either side of center mark, drill Ø25x15mm hole. Use strike as guide to mark and chisel recess, drill pilot holes and screw in strike.




## 6. INSTALL FURNITURE

Attach furniture. If installing a privacy set, ensure the privacy lever is positioned on the inside of the door.




## 7. INSTALL FURNITURE




## 8. ROTATE BEZEL

Rotate bezel to lock in place.




## 9. TIGHTEN SCREWS




## 10. FIT ANTI-ROTATIONAL SCREWS

OPTIONAL



## 11. FIT ROSE COVER



## 12. FIT PRIVACY PIN

PRIVACY ONLY

