





Legge's 995V narrow stile mortice vestibule lock has been designed on the underlying successful design principles of the 990MF Series. Manufactured specifically to meet the requirements of the Australasian market, the 995V provides the specifier and end user with a combination lock for both metal and timber doors. The 995V is ideally suited for commercial and industrial applications where durability and security are of major importance.

The 995V has a high purity die cast zinc alloy case to provide rigidity and precision. Major internal components are made of either stainless steel or sintered steel/ copper alloy to provide durability and strength.

The final product has been rigorously tested in accelerated wear tests and testimony to the quality of the 995MF Series is shown through the extensive use in the Australian and New Zealand markets.







- Designed to suit hollow stile metal door sections with internal depths from 39mm and narrow stile timber and french doors
- The multi-function case allows easy conversion of a vestibule lock function (inside handle free) to a combination lock function (both handles locked) by a simple external operation
- The reversible stainless steel latch adjusts for inwards/outwards opening and left/right hand without case disassembly
- The latch is deadlatched by a stainless steel subbolt that retracts automatically with the main latch
- The 995MF case will accept bolt-through fixing for 159mm vertical fixing door furniture such as the Legge 5300/5400 Series narrow stile furniture
- Follower will accept 7.6mm-8mm furniture spindles, with no adjustment necessary
- A threaded pin is used for secure cylinder retention
- Designed to be compatible with most electric strikes

	Warranties		
Mechanical	30 years		
Finish	allegion.co.nz/finisheswarranty		



Specification guide

Select the desired backset e.g. 30mm

	Function	Sub-function	Faceplate	Finish	Backset
- 1	Vestibule lockL9V	Vestibule lock .V1(RH)/V2(LH) Double cylinder lock .V7(RH)/V8(LH) Storeroom lock .V9(RH)/V10(LH) Single action lock .V11(RH)/V12(LH) Entrance lock .V21(RH)/V22(LH) Office/classroom lock .V31(RH)/V32(LH) Egress lock .V41(RH)/V42(LH) Secure egress lock .V49(RH)/V50(LH) Exit latch .V55(RH)/V56(LH)	Metal fix (short)blank Wood fix (long)W	Antique BronzeABZ Chrome PlateCP Oil Rubbed BronzeORB Polished BrassPB Satin Black ChromeSBC Satin BrassSB Satin Brass UnlacqueredSBU Satin Chrome PlateSCP	23mmstandard 30mm30 38mm38
1	I. Function Select the desired function e.g. Vestibule lockL9V				
2	2. Sub-function Select the required sub-function e.g. V31 Office/classroom lock				
3	3. Faceplate Select the desired faceplate e.g. Wood fix				
4	4. Finish Select the desired finish e.g. Satin chrome plateL9V31WS				
5	5. Backset				

Finishes



Testing and Compliance



Security:

Rated $\tilde{S}8$ and SL8 for physical security, SC7–SC8 for cylinder security and K6 for keying security



Corrosion:

Rated C7 for corrosion




Durability:

Rated D8 for durability



.....L9V31WS30


Legge 995V Vestibule Lock





- Inside handle always operative for emergency escape
- Automatic deadlocking by closing door
- Reversible bolt and function

Specifications

Door type	type Timber or metal	
Door thickness	Timber doors - 32mm to 48mm standard. Extended cylinders, spindles and strike plates available. Metal doors - 35mm to 48mm standard. Designed to be used on hollow stile door sections, with a minimum internal depth of 39mm.	
Lock case	High purity zinc alloy	
Outer forend	Satin stainless steel or brass	
Bolt	Stainless steel	
Sub-bolt	Stainless steel	
Spindles	2 split spindles 32mm	
Strike plate	Satin stainless steel or brass	
Backsets	23mm standard. 30mm and 38mm available	
Key cylinder	C4 6 Pin keyway standard, Schlage C6 pin keyway optional, Schlage SR1 Restricted keyway optional, Schlage Everest Open & Restricted keyways optional	







Legge 995V Vestibule Lock

Sub-function Cams and adaptors

V1 (RH) V2 (LH) - Vestibule lock

Outside: Key operates bolt at all times. Handle operative except when locked by inside turn Inside: Turn locks and unlocks outside handle. Handle always operative



V7 (RH) V8 (LH) - Double cylinder lock

Outside: Key retracts bolt at all times. Handle operative except when locked by inside key Inside: Key locks and unlocks outside handle. Inside handle always operative



V9 (RH) V10 (LH) - Storeroom lock

Outside: Key operates bolt at all times. Handle always inoperative Inside: Handle always operative



V11 (RH) V12 (LH) - Single action lock

Outside: Key operates bolt at all times Inside: Handle always operative



V21 (RH) V22 (LH) - Entrance lock

Outside: Key locks or unlocks outside handle Inside: Turn locks and unlocks outside handle. Inside handle always operative




Legge 995V Accessories

Long lipped strike


Strikes for non-standard wooden jambs. Available in 50mm, 60mm, 70mm, 80mm & 90mm (A)

Finishes Satin chrome plate, for special finishes available refer to page 2



Short lipped strike

Strikes for non-standard jambs Finishes Satin chrome plate, for special finishes available refer to page 2





Legge 995V Vestibule Lock

Sub-function Cams and adaptors

V31 (RH) V32 (LH) - Office/classroom lock

Outside: Key locks and unlocks handle. Handle operative except when locked by outside key Inside: Handle always operative



V41 (RH) V42 (LH) - Egress lock

Outside: Handle operative except when locked by inside turn Inside: Turn locks and unlocks outside handle. Inside handle always operative



V49 (RH) V50 (LH) - Secure egress lock

Outside: Handle operative except when locked by inside key Inside: Key locks and unlocks outside handle. Inside handle always operative



V55 (RH) V56 (LH) - Exit latch

Outside: Handle always inoperative Inside: Handle always operative



Legge 995V Cams and cam adaptors

2 5 6A (with adaptor)









